



Aquascape Engineers

Aquascape
India

An ISO 9001 : 2000 Company

Spray Rings
PF 9000 Series


Design and application Data

Spray rings are constructed of stainless steel, brass and copper in a variety of diameter and orifice sizes. Adjustable brass smooth stream nozzles develop uniform circular spray pattern.



Notes

- Specify : Spray ring materials like Brass, Copper or Stainless Steel
- Specify : Dome center Drop, Inside Drop, Outside drop, Vertical Pattern, Inside Basket weave, outside basket weave.
- Nozzle angle can be adjusted after installation.
- Provide basket strainer or 'Y' type strainer for nozzle orifice protection



Hydraulic Data

Model No.	Diameter	Type of Nozzles	Jet Orifice	Qty. of Nozzles		Spray Height in Meter						
						0.50	1.00	1.50	2.00	2.50	3.00	4.00
PF-9012	300 mm	PF-1010	4.75 mm	12	LPM	68	95	104	117	140	180	225
					Head in Mtr	1.82	3.04	3.65	4.87	5.60	5.90	6.00
PF-9018	450 mm	PF-1010	4.75 mm	18	LPM	102	143	156	176	210	270	330
					Head in Mtr	1.82	3.04	3.65	4.87	5.60	5.90	6.00
PF-9024	600 mm	PF-1010	4.75 mm	24	LPM	136	190	208	235	280	360	440
					Head in Mtr	1.82	3.04	3.65	4.87	5.60	5.90	6.00
PF-9030	750 mm	PF-1010	4.75 mm	22	LPM	136	190	208	235	280	360	440
					Head in Mtr	1.82	3.04	3.65	4.87	5.60	5.90	6.00
PF-9036	900 mm	PF-1010	4.75 mm	27	LPM	153	214	234	265	316	405	495
					Head in Mtr	1.82	3.04	3.65	4.87	5.60	5.90	6.00
PF-9048	1200 mm	PF-1010	4.75 mm	36	LPM	204	286	313	353	421	540	660
					Head in Mtr	1.82	3.04	3.65	4.87	5.60	5.90	6.00
PF-9060	1500 mm	PF-1011	6.35 mm	45	LPM	476	578	680	850	1020	1035	1095
					Head in Mtr	1.82	3.04	3.65	4.87	5.60	5.90	6.00
PF-9072	1800 mm	PF-1011	6.35 mm	54	LPM	571	693	816	1020	1224	1428	1700
					Head in Mtr	1.82	3.04	3.65	4.87	5.60	5.90	6.00
PF-9096	2400 mm	PF-1011	6.35 mm	72	LPM	761	925	1088	1360	1632	1728	1850
					Head in Mtr	1.82	3.04	3.65	4.87	5.60	5.90	6.00
PF-9120	3000 mm	PF-1011	6.35 mm	90	LPM	952	1156	1360	1701	2041	2160	2350
					Head in Mtr	1.82	3.04	3.65	4.87	5.60	5.90	6.00